



Quality is in our nature

PRODUCT INFORMATION

September 2014



EUROL HD 20W-50

Mineral motor oil for Harley Davidson motorcycles

Eurol® Harley Davidson oil has especially been developed for Harley Davidson motorcycles. This oil is formulated with selected base stocks and additives, reducing oil consumption to a minimum.

Eurol® Harley Davidson oil has been applied for the lubrication of Harley Davidson motorcycles successfully, for many years.

Eurol® Harley Davidson withstands heavy shock loads and offers good protection against corrosion and oxidation, so wear is reduced to a minimum. In short: a robust oil for a perfect lubrication which enables the Harley Davidson to last for years.

PERFORMANCE

Specifications Monograde 50 and 60

API SF/CC

JASO MA2

JASO MA

Specifications 20W-50 and 20W-60

API SG/CD

JASO MA2

JASO MA

TYPICAL PROPERTIES

		SAE 50	SAE 60	20W-50	20W-60
Density 20C	Kg/L	0.890	0.900	0.883	0.884
Viscosity 100C	cSt	17.1	24.0	17.9	24.0
Viscosity 40C	cSt	180	338	161	208
Viscosity -15C	cP	-	-	<9500	<9500
Viscosity Index		101	95	123	143
Flash point COC	C	248	267	226	230
Pour point	C	-18	-18	-24	-20

AVAILABLE VOLUMES

E100390 - 1L, E100390 - 4L, E100390 - 60L, E100390 - 210L



The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of Eurol products. The information in this document at any time and without notice be altered because of continuous product research and development. The analytical data are listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, the quality of the product does not affect. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product in consultation with the supplier.